

# UK DECLARATION OF PERFORMANCE

CPR 2011 (Retained EU law 305/2011) as amended



No.: 129

1. **Unique identification code of the product-type** RAIS VISIO Uniq 3:1 - ATTIKA VISIO Uniq 3:1
2. **Type** Inset appliance burning solid fuel without hot water supply
3. **Intended use** Domestic room heater
4. **Manufacturer** Spartherm Feuerungstechnik GmbH, Maschweg 38, D-49324 Melle, [www.spartherm.com](http://www.spartherm.com)
5. **Authorised representative** RAIS A/S, Industrivej 20, Vangen, DK-9900 Frederikshavn, Dänemark, [www.rais.com](http://www.rais.com) / [www.attika.ch](http://www.attika.ch)
6. **System of assessment AVCP** System 3  
Approved Body – *Danish Technological Institute - Identification no. 1235*  
*Teknologiparken, Kongsvang Allé 29, DK-8000 Århus C, Danmark*  
*Test report: 300-ELAB2646-EN*
7. **Approved Body** performed the determination of the product type on the basis of type testing under system 3 and issued test report
8. **Declared performance** Harmonized technical specification: EN 13229:2001/A2:2004/AC:2007

Essential characteristics		Performance
Fire safety		<ul style="list-style-type: none"><li>Insulated flue</li><li>50 mm Skamotec 225 non-combustible panel board</li></ul> Distances are measured externally on the built-in box
Reaction to fire	A1	<b>Visio Uniq 3:1</b>
Distance to combustible materials	rear	0
Minimum distances [mm]	sides	600
<i>For other installation or wall settings see instruction manual</i>	Front	800
	Ceiling	380
	Floor	400
Risk of burning fuel falling out	Pass	
OGC (mg/Nm <sup>3</sup> rel. 13 Vol-% O <sub>2</sub> )	≤ 120	
CO-emission of combustion products	≤ 0,12 % / ≤ 1500 mg/Nm <sup>3</sup>	
NO <sub>x</sub> (mg/Nm <sup>3</sup> rel. 13 Vol-% O <sub>2</sub> )	≤ 200	
Dust mg/Nm <sup>3</sup> at (rel. 13 Vol-% O <sub>2</sub> )	≤ 40	
Surface temperature	Pass	
Electrical safety	NPD	
Cleanability	Pass	
Maximum operating pressure	- bar	
Flue gas temperature T at nominal heat output	262 °C	
Mechanical resistance (to carry a chimney/flue)	NPD	
<b>Thermal output</b>		
Nominal heat output	11,3 kW	
Room heating output	11,3 kW	
Water heating output	- kW	
Energy efficiency <sup>17</sup>	≥ 75 %	
Seasonal Efficiency $\eta_{S,on}$	≥ 65 %	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D Manager

Place FREDERIKSHAVN, DENMARK

Date 01-12-2023

  
Signature